

TUCKUNDER[™] SERIES

LIFTING CAPACITIES (LBS): 1500, 2000, 2500, 3000



KEY ADVANTAGES

Shown with optional features.

- 1. **HD Mechanical Safety Latch** Redundant-system stowage in addition to hydraulic lock.
- 2. Spring Assist Platform Dual torsion springs provide effortless platform operation.
- 3. EZ Mount

Ships factory assembled, filled, and tested with notched center mark for easy installation. Floor extension may be bolted to the truck.

4. CHS - Centralized Hydraulic System All sensitive hydraulic and electrical compone

All sensitive hydraulic and electrical components housed safely within the stainless steel pump box.

MADE IN THE USA

5. **Lifetime-Warranty Service Free Bushings** Used at all critical pivot points to reduce wear without the need for routine lubrication.

QUALITY, RELIABILITY, CUSTOMER SERVICE

STANDARD FEATURES

- Circuit Protection

200 Amp fuse protects truck wiring from a "dead short".

- Marine Duty Potted Toggle Switch
 Heavy duty toggle, potted to permanently separate and seal electrical connections from corrosion.
- **3/16" Steel Floor Extension** Rugged and attractive surface.

Industry-Leading Warranty 2 years mechanical + 2 years electrical & hydraulic, parts and labor.

Pressure Compensated Flow Valve Constant, controlled speeds at all times. Prevents "free-fall" under certain hydraulic failures.

 Anthony 3-Step Powder Coat
 Steel components are washed, shot blast prepped, and coated with premium finish.

QUALITY COMES STANDARD

AVAILABLE MODELS, PLATFORMS AND CAPACITIES

Model	AST-1500	AST-2000	AST-2500	AST-3000	
Capacity (lbs)	1500	2000	2500	3000	
Bed Height Range	42" - 57"				
Available Platforms					
Steel 80" x 38" + 5" Ramped					
Steel 80" x 50" Wedge*					
Aluminum 80" x 50" Wedge*					
Model		ASTL-1800	А	STL-2500	
Capacity (lbs)		1800		2500	
Bed Height Range	ge 36" - 44"				
	Availab	le Platforms			
Steel 80" x 44" Wedge (standard)					

Aluminum 80" x 44" Wedge


OPTIONS

- Cart stops
- Power down
- Max Duty dock bumpers
- Rubber bumper pads
- Alternate floor extensions: 3/16", 1/4", or 3/8" steel. 96" or 102" Wide
- Wireless, removable handheld corded, flush mount, or dual control options.
- Stainless steel toggle switch guard
- Third step add-on for dock bumper
- Galvanized finish with extended warranty
- ICC bumper
- Cab or ignition cutoff switch
- 5 & 12 ton pintle hook / ball hitch brackets
- Walkramp capability
- Battery box

*Cart stops available. 39" load area when deployed.

TRUCK MOUNTING REQUIREMENTS

		С	В	Α
1	Ť	Mounting Plate	Bed to Top of Tube Assembly	Bed Height
B		29"	15 3/4"	36"- 41"
Ļ		24 1/4"	19"	42"- 49"
	Α	23 3/4"	20″	50"- 51"
Liftgate Mounting Pla		23 1/4"	21″	52"- 53"
Pump B		22 5/8"	22″	54"- 55"
Forward	ļ	22 1/2"	23″	56"- 57"



Anthony Liftgates, Inc.

1037 W. Howard Street P.O. Box 615 Pontiac, IL 61764-0615 **Phone:** 815.842.3383

Fax: 815.844.3612

Toll Free: 800.482.0003

www.anthonyliftgates.com

06/14 © 2014 Anthony Liftgates, Inc.® A-136004 Printed in USA.